

RAMIFICAȚIE LA 45°



DN/DN [mm]	DN/DN [mm]	DN/DN [mm]
110/110	315/110	500/110
125/110	315/125	500/160
125/125	315/160	500/200
160/110	315/200	500/250
160/125	315/250	500/315
160/160	315/315	500/400
200/110	400/110	500/500
200/160	400/125	
200/200	400/160	
250/110	400/200	
250/160	400/250	
250/200	400/315	
250/250	400/400	

RAMIFICAȚIE LA 87°



DN/DN [mm]	DN/DN [mm]	DN/DN [mm]
110/110	315/110	500/160
125/110	315/125	500/200
125/125	315/160	500/250
160/110	315/200	500/315
160/125	315/250	500/400
160/160	315/315	500/500
200/110	400/110	
200/160	400/125	
200/200	400/160	
250/110	400/200	
250/160	400/250	
250/200	400/315	
250/250	400/400	

ȘA BRANȘARE PVC LA 45° SAU 87°



DN/DN [mm]	DN/DN [mm]
125/110	315/160
160/110	315/200
200/110	400/160
200/125	400/200
200/160	
250/160	
250/200	

REDUCȚIE

DN [mm]
110
125
160
200
250
315
400
500



MUFĂ DUBLĂ

DN [mm]
110
125
160
200
250
315
400
500



DOP

DN [mm]
110
125
160
200
250
315
400
500



PIESĂ LEGĂTURĂ FONTĂ / KG

DN [mm]
110
125
160
200



PIESĂ LEGĂTURĂ BETON/ KG

DN [mm]
110
125
160
200
250
315



PIESĂ CURĂȚIRE

DN [mm]
110
125
160
200
250
315



PIESĂ TRECERE PRIN CĂMIN

DN [mm]
110
125
160
200
250
315
400
500



CLAPETĂ ANTIREFULARE

DN [mm]
110
125
160
200

